


Product Data Sheet (2021-07-19)

Airfix 2 - 4

Small vessels for use in oxygen rich water installations (the vessels are not flow through and therefore not suitable for potable water for the German market).



Type	Pre-charge [bar]	Dimensions		Connection	Weight [kg]		Order Code
		Ø [mm]	H. [mm]				
Airfix 2 - 4.0 bar	4	216	144	G $\frac{3}{4}$ " M	1.7	120	24001
Airfix 2 - specify	*	216	144	G $\frac{3}{4}$ " M	1.7	120	24002
Airfix 4 - 4.0 bar	4	216	194	G $\frac{3}{4}$ " M	2.1	90	24101
Airfix 4 - specify	*	216	194	G $\frac{3}{4}$ " M	2.1	90	24102

* Gas charge must be stated on order.



Advantages

- Nitrogen gas filling for longer retention of pre-charge.

Technical Specifications

- Maximum working pressure: 6.0 bar.
- Minimum / maximum working temperature (diaphragm): 1 / 70 °C.
- Colour: White, RAL 9010.
- In accordance with Pressure Equipment Directive 2014/68/EU.

Find more information online:

[Installation and operating instruction](#)

[?????](#)

[Export catalogue](#)

Flamco Group
Fort Blauwkapel 1
1358 DB, Almere - nl
T +31 (0)36 52 62 300
E info@flamcogroup.com
I flamcogroup.com